Journal of Nonlinear Analysis and Optimization Vol. 13, Issue. 2 : 2022 ISSN : **1906-9685** 



#### MODELING AND THERMAL ANALYSIS OF HEAD ENGINE GASKETS

Dr.CH.Shashikanth, Associate professor, Department Of Mechanical Engineering Sree Chaitanya College of Engineering, Karimnagar

P.Anitha, Assistant professor, Department Of Mechanical Engineering Sree Chaitanya College of Engineering, Karimnagar

Abstract In an engine, a gasket is located between the cylinder head and engine block. Its goal is to seal the cylinders to guarantee optimal compression and prevent coolant or engine oil from leaking inside the cylinders. I would like to change the gasket of a four-cylinder engine's material and design based on our idea. Multiple Layers, or MLS Steel (they are usually made of three layers) and asbestos The majority of contemporary head engines are made using MLS gaskets. The thicker center layer is left uncovered and the contact faces are often covered with a rubber-like coating, such as Viton, that sticks to the cylinder block and cylinder head. Gasket producers are compelled to search for asbestos substitutes due to the health hazards associated with fine asbestos fibers. to subject the four-stroke engine's cylinder head gasket to a thermal analysis test.

This examination can be used to compare various gasket materials and determine which cylinder head gasket problems arise from. The temperature differential is mostly to blame for the deformation of the gasket materials. This report introduces the numerical simulation of the thermal analysis using the commercial program ANSYS. The Catia software is used to create the gasket diagram. Analysis is done using the software's loaded diagram. ANSYS is used to compare the performance of these three materials and determine which is superior. In this project, different optimization techniques are applied by changing the gasket's material. Design software is used for the modeling of gaskets. The ANSYS finite element analysis was used to improve the gasket material's thermal and structural qualities.

Keywords: Ansys, Catia, Transient Thermal, and Gasket.

#### **I INTRODUCTION**

A gasket is a mechanical seal which fills the space between two or more mating surfaces, generally to prevent leakage from or into the joined objects while under compression. It is a deformable material that is used to create a static seal and maintain that seal under various operating conditions in a mechanical assembly. Gaskets allow for "less-than-perfect" mating surfaces on machine parts where they can fill irregularities. The engine of an automobile is divided into a cylinder head ("head") and a cylinder block ("block").

A cylinder head gasket ("gasket") is inserted between the head and the block to prevent leaks of the high-pressure combustion gas, cooling water, etc. inside the engine. Its purpose is to seal the cylinders to ensure maximum compression and avoid leakage of coolant or engine oil into the cylinders; as such, it is the most critical sealing application in any engine and, as part of the combustion chamber, it shares the same strength requirements as other combustion chamber components.



## Fig 1: Engine Block

The condition of a head gasket is typically investigated by checking the compression pressure with a pressure gauge, or better, a leak-down test, and/or noting any indication of combustion gases in the cooling system on a water-cooled engine. Oil mixed with coolant and excessive coolant loss with no apparent cause, or presence of carbon monoxide or hydrocarbon gases in the expansion tank of the cooling system can also be signs of head gasket problems.

## Gasket Design

Every application requires a unique cylinder head gasket design to meet the specific performance needs of the engine. The materials and designs used are a result of testing and engineering various metals, composites and chemicals into a gasket that is intended to maintain the necessary sealing capabilities for the life of the engine. Head gasket designs have changed over time to time, and in recent years are changing even faster.

The most widely used materials are as follows:

- 1. Copper and Asbestos combination.
- 2. Fiber based composite materials. Graphite in various densities.
- 3. Combination of Aluminium and Fiber.

## Properties of a Gasket used

The gasket material should have good flexibility, low density, and high tensile strength. It should also have a resistance to chemicals and internal pressure, and durability. It must also have excellent adhesion properties with itself and anything it touches. Excellent wear resistance. Good bonding strength. Not as ideally suited to mechanical, weathering and chemical resistance.

## **II LITERAURE STUDIES**

**V. Arjun, Mr. V.V. Ramakrishna, Mr. S. Rajasekhar, al. [2015],** Thermal Analysis of an Engine Gasket at Different Operating Temperatures, Gasket sits between the engine block and cylinder head in an engine. Its purpose is to seal the cylinders to ensure maximum compression and avoid leakage of coolant or engine oil into the cylinders. From our project, we would like to modify the material and design of the gasket of four-cylinder engine.

**M.Srikanth1 B.M. Balakrishnan2, al. [2015],** Cylinder Head Gasket Analysis to Improve its Thermal Characteristics Using Advanced Fem Tool, Gasket sits between the engine block and cylinder head in an engine. Its purpose is to seal the cylinders to ensure maximum compression and avoid leakage of coolant or engine oil into the cylinders. From our project, we would like to modify the material and design of the gasket of four-cylinder engine. MLS or Multiple Layers Steel (These typically consist of three layers of steel) and asbestos – Most modern head engines are produced with MLS gaskets.

**Dr M K Rodge et al (2016):** In this paper we have considered the multilayer cylinder head gasket of single cylinder diesel engine for the analysis. Nonlinear analysis for the cylinder head gasket is performed to reduce the bore distortion as well as to achieve the optimum contact pressure on the cylinder head gasket. Modelling has done in the CRE-O 2.0 and for the analysis ANSYS 15 software is used.

## III METHODOLOGY USED

To obtain total deformation of the gasket we have taken four different materials having different properties. Materials that we selected is Stainless steel, Ceramic8D, FR-4 Epoxy, Steel 1008. With

these materials we are going to analysing the thermal expansion of gasket and to find the thermal stress and temperature deformation, total heat flux and thermal error for these four materials of gasket, by comparing these four material results. distribution which material is good and cost reduction.

#### Materials Used in this study

**Ceramic8D:** A ceramic is an inorganic non-metallic solid made up of either metal or non-metal compounds that have been shaped and then hardened by heating to high temperatures. In general, they are hard, corrosion-resistant and brittle. Ceramics generally can withstand very high temperatures, ranging from 1,000 °C to 1,600 °C (1,800 °F to 3,000 °F).

**FR-4 Epoxy:** FR4 is a class of printed circuit board base material made from a flame-retardant epoxy resin and glass fabric composite. FR stands for flame retardant and meets the requirements of UL94V-0. FR4 has good adhesion to copper foil and has minimal water absorption, making it very suitable for standard applications.

**Steel 1008:** Steels containing mostly carbon as the alloying element are called carbon steels. They contain about 1.2% manganese and 0.4% silicon. Nickel, aluminium, chromium, copper and molybdenum are also present in small quantities in the carbon steels. AISI 1008 carbon steel has excellent weldability, which includes projection, butt, spot and fusion, and braze ability. It is primarily used in extruded, cold headed, cold upset, and cold pressed parts and forms.

**Steel Stainless:** Stainless steels are steels containing at least 10.5% chromium, less than 1.2% carbon and other alloying elements. Stainless steel's corrosion resistance and mechanical properties can be further enhanced by adding other elements, such as nickel, molybdenum, titanium, niobium, manganese, etc. This metal derives its name because it does not stain, rust or corrode, hence, called "STAINLESS STEEL".

#### Developed model in ANSYS software



Fig 2: Gasket in ANSYS

#### IV RESULTS AND DISCUSSIONS Material: Stainless steel



Fig 4: Temperature





#### Fig 5:Convection







## **Graph2:** Temperature - Global Minimum vs Time **Table 1:** Results (Stainless steel)





Graph 3:Temperature Vs Time



Graph 6: Thermal Error Vs Time

#### Material: Steel 1008



Fig 9: Mesh model for steel 1008



#### Fig 10: Temperature



#### Fig 11: Convection



#### Graph 7: Temperature - Global Maximum vs Time



## Graph 8:Temperature - Global Minimum vs Time Table 2: Results (Steel 1008)

Object Name	Temperature	Total Heat Flux	Directional Heat Flux	Thermal Error				
State	Solved							
Results								
Minimum	141.64 °C	3.0497e-008 W/mm <sup>2</sup>	-1.6108e-002 W/mm <sup>2</sup>	3.1384e-007				
Maximum	142. °C	1.6108e-002 W/mm <sup>2</sup>		4.1479e-002				
Minimum Value Over Time								
Minimum	-0.35455 °C	3.0497e-008 W/mm <sup>2</sup>	-6.406 W/mm <sup>2</sup>	3.1384e-007				
Maximum	141.64 °C	1.4898e-005 W/mm <sup>2</sup>	-1.6108e-002 W/mm <sup>2</sup>	2.0446e-002				
Maximum Value Over Time								
Minimum	142. °C	1.6108e-002 W/mm <sup>2</sup>		4.1479e-002				
Maximum	142. °C	6.406 W/mm <sup>2</sup>	6.4059 W/mm <sup>2</sup>	336.07				
Information								
Time			1. s					





Graph 9: Temperature Vs Time



Fig 13: Total Heat Flux







Fig 14: Directional Heat Flux



Graph 11:Directional Heat Flux vs time



Fig 15: Thermal Error



Graph 12:Thermal Error Vs Time Material: FR-4 Epoxy



Fig 17: Temperature



#### Fig 18: Convection



#### Graph 13: Temperature - Global Maximum vs Time



## Graph 14:Temperature - Global Minimum vs time Table 3: Results (FR-4 Epoxy)



#### Fig 19: Temperature



Graph 15: Temperature Vs Time



## Fig 20: Total Heat Flux



Graph 16: Total Heat Flux vs time



Fig 21: Directional Heat Flux



Graph 17:Directional Heat Flux Vs Time



Fig 22: Thermal Error



# Graph 18:Thermal Error Vs Time Material : Ceramic8D



#### Fig 23: Mesh model



#### Fig 24: Temperature



#### Fig 25: Convection



#### Graph 19: Temperature - Global Maximum vs Time



Graph 20: Temperature - Global Minimum vs Time

#### Table 4: Results (Ceramic8D)



Fig 25: Temperature



#### Graph 21: Temperature Vs Time



Fig 26: Total heat flux



Graph 22: Total Heat Flux vs time







Graph 23: Directional Heat Flux Vs Time



Fig 28: Thermal Error



Graph 24: Thermal Error Vs Time

#### **Results and Comparison Table 5:** Ceramic8D Results

	Object Name	Temperature	Total Heat Flux	Directional Heat Flux	Thermal Error			
	Results							
	Minimum	64.673 °C	0.19279 W/m <sup>2</sup>	-3.4797e+005 W/m <sup>2</sup>	3.5659e-007			
	Maximum	142. °C	3.4798e+005 W/m2	3.4797e+005 W/m2	4.8677e-002			
Table 6: FR-4 Epoxy Results								
	Object Name	Temperature	Total Heat Flux	Directional Heat Flux	Thermal Error			
	Results							
	Minimum	1.8734 °C	6.5119e-002 W/m <sup>2</sup>	-41197 W/m <sup>2</sup>	2.3816e-007			
	Maximum	142. °C	41197 W/m <sup>2</sup>		1.1897e-003			

#### Table 7: Steel 1008

Object Name	Temperature	Total Heat Flux	Directional Heat Flux	Thermal Error				
Results								
Minimum	141.64 °C	3.0497e-002 W/m <sup>2</sup>	-16108 W/m <sup>2</sup>	3.1384e-010				
Maximum	142. °C	16108 W/m <sup>2</sup>		4.1479e-005				
Table 8: Steel Stainless								
Object Name	e Temperature	Total Heat Flux	Directional Heat Flux	Thermal Error				
	Results							
Minimum	121.18 °C	0.89648 W/m <sup>2</sup>	-2.8736e+005 W/m <sup>2</sup>	1.2887e-007				
Maximum	n 142. °C	2.8736e+005 W/m <sup>2</sup>		2.9437e-002				

### **V CONCLUSIONS**

The thermal condition of the cylinder head gasket composed of Steel Stainless and Ceramic8D, FR-4 Epoxy, and Steel 1008 material was effectively analyzed in this project. By contrasting the aforementioned findings, it can be seen that Steel 1008 is low in heat flow and can tolerate high temperatures. The thermal error is appropriate for manufacturing head gaskets at high temperatures and low heat fluxes. Based on this, we have determined that Steel 1008 is a good substitute material. As a result, there will be fewer gasket breaks and the engine will last longer.

by examining how well the cylinder head gasket seals using different materials. Enhancement of the sealing joints is feasible. This will lower expenses, shorten the time needed for development, and enhance engine performance and gasket reliability. in additional improvements made possible by this project.

The distortion of the gasket is caused by more than just temperature. Another factor contributing to the gasket's distortion is the pressure inside the cylinder.

#### REFERENCES

[1] Mr. V.V. Ramakrishna, Mr. S. Rajasekhar, (December 2015) "Thermal Analysis of an Engine Gasket At Different Operating Temperatures" issue 12, ISSN 2348 – 4845.

[2] G.P. Blair, C.D. McCartan, H. Hermann, (July 2005) "The Right Lift", Race Engine Technology, issue 009, ISSN 1740 -6803

[3] T.Belytschko, W.K. Liu, B.Moran,(2010) Nonlinear Finite Elements for Continua and Structures, Wiley, New York, 2000pp. 569 -613.

[4] Bormane, G., Nishiwaki, K. (2011) "Internal Combustion Engine Heat Transfer", ProgEnergycombustion Science, vol.13, PP.1 -46.

[5] B. Corona, M. Nakano, H. Pérez, (2007) "Adaptive Watermarking Algorithm for Binary Image Watermarks", Lecture Notes in Computer Science, Springer, pp. 207-215.

[6] S.K. Chan, I.S. Tuba, (2008) A finite element method for contact problem of solid bodies part -1, theory and validation, Int. J. Mech. Sci. 18 (13) 615 - 625.

[7] R.Jonathan,(2011) Modeling diesel engine cylinder head gaskets using the gasket material option of the SOLID185 element, ANAYS User's Conference.

[8] F.Macek Heat,(2003) "Analysis of Engine Head gasket", Abstracts of 20th Danubia Adria Symposium on Experimental Methods in Solid Mechanics. University of Applied Sciences, s. 74 - 75. ISBN 963 -9058 -20.

[9] J.Montgomery, (2002) Methods for modeling bolts in the bolted joint, ANSYS User's Conference.

[10] A.R.Mijar, J.S. Arora,(2008) review of formulations for elastostatic frictional contact problems, Struct. Multidiscip. Optim. 167 -189.

[11] S.Othe,(2008) Finite element analysis of elastic contact problems, Bull. JSME 16 (95) 797 -804.[12] Raub, J. H. (2006), "Structural Analysis of Diesel Engine Cylinder Head Gasket Joints," SAE Paper 921725