

DENSITY BASED TRAFFIC CONTROL SYSTEM USING CANNY EDGE DETECTION ALGORITHM

Dr.B.Sarada, P.Bhavana, D.Indu, N.Satwika, R.Lakshmi

¹Assitsant Professor, ^{2,3,4,5}UG Students, Dept. Computer Science and Engineering-Data Science, Mallareddy Engineering college for Women, Hyderabad, India.

Abstract

As the problem of urban traffic congestion intensifies, there is a pressing need for the introduction of advanced technology and equipment to improve the state-of-theart of traffic control. The current methods used such as timers or human control are proved to be inferior to alleviate this crisis. In this paper, a system to control the traffic by measuring the realtime vehicle density using canny edge detection with digital image processing is proposed. This imposing traffic control system offers significant improvement in response time, vehicle management, automation, reliability and overall efficiency over the existing systems. Besides that, the complete technique from image acquisition to edge detection and finally green signal allotment using four sample images of different traffic conditions is illustrated with proper schematics and the final results are verified by hardware implementation In this project we are describing concept to control or automate green traffic signal allotment time based on congestion available at road side using Canny Edge Detection Algorithm To implement this technique we are uploading current traffic imageto the application andwill extract edges from images and if there is more traffic then will be more number of edges with white colour and if uploaded image contains less traffic then it will have less number of white colour edges Empty edges will have black colour with value 0. By counting number of non-Zeroes white pixels we will have complete idea of available traffic and based on that we will allocate time to green signal. If less traffic is there then green signal time will be less otherwise green signal allocation time will be more.

Introduction

Traffic congestion is one of the major modern-day crisis in every big city in the world. Recent study of World Bank has shown that average vehicle speed has been reduced from 21 km to 7 km per hour in the last 10 years in Dhaka [1]. Intermetropolitan area studies suggest that traffic congestion reduces regional competitiveness and redistributes economic activity by slowing growth in county gross output or slowing metropolitan area employment growth [2]. As more and more vehicles are commissioning in an already congested traffic system, there is an urgent need for a whole new traffic control system using advanced technologies to existent infrastructures to its full extent. Since building new roads, flyovers, elevated expressway etc. needs extensive planning, huge capital and lots of time; focus should be directed upon availing existing infrastructures more efficiently and diligently. Previously differenthad been proposed, such as infra-red light sensor, induction loop etc. to acquire traffic date which had their fair share of demerits. In recent years, image processing has shown promising outcomes in acquiring real time traffic information using CCTV footage installed along the traffic light. Different approaches have been proposed to glean traffic data. Some of them count total number of pixels [3], some of the work calculate number of vehicles These methods have shown promising results in collecting traffic data. However, calculating the number of vehicles may give false results if the intravehicular spacing is very small (two vehicles close to each other http://doi.org/10.36893/JNAO.2023.V14I2.0092-0099

may be counted as one) and it may not count rickshaw or auto-rickshaw as vehicles which are the quotidian means of traffic especially in South-Asian And counting number of pixels has disadvantage of counting insubstantial materials as vehicles such as footpath or pedestrians. Some of the work have proposed to allocate time based solely on the density of traffic. But this may be disadvantageous for those who are in lanes that have less frequency of traffic. Edge detection technique is imperative to extract the required traffic information from the CCTV footage. It can be used to isolate the required information from rest of the image. There are several edge detection techniques available.

They have distinct characteristics in terms of noise reduction, detection sensitivity, accuracy etc. Among them, Prewitt [7], canny [8],Sobel [9], Roberts and LOG are most accredited operators. It has been observed that the Canny edge detector depicts higher accuracy in detection of object with higher entropy, PSNR(Peak Signal to Noise Ratio), MSE(Mean Square Error) and execution time compared with Sobel, Roberts, Prewitt, Zero crossing and LOG.INDIA is the second most populous Country in the World and is a fast growing economy. It is seeing terrible road congestion problems in its cities. Infrastructure growth is slow as compared to the growth in number of vehicles, due to space and cost constraints [1]. Also, Indian traffic is non lane based and chaotic. It needs a traffic control solutions, which are different from the developed Countries. Intelligent management of traffic flows can reduce the negative impact of congestion

EXISTINGSYSTEM

Previously different techniques had been proposed, such as infra-red light sensor, induction loop etc. to acquire traffic date which had their fair share of demerits. In recent years, image processing has shown promising outcomes in acquiring real time traffic information using CCTV footage installed along the traffic light.

Differentapproacheshavebeenproposedtogleantrafficdata.Someofthemcounttotalnumberofpixels[3],someofth eworkcalculate number of vehicles [4- 6].These methods have shown promising results in collecting traffic data.

However, calculating the number of vehicles may give false results if the intravehicular spacing is very small (two vehi clesclose to each other may be counted as one) and it may not count ricks haw or auto-ricks haw as vehicles which are the quotidian means of traffic especially in South-Asian countries. And counting number of pixels has disadvantage of counting insubstantial materials as vehicles such as footpath or pedestrians. Some of the work have proposed to allocate time based solely on the density of traffic. But this may be disadvantageous for those who are in lanes that have less frequency of traffic

PROPOSED SYSTEM

Edge detection technique is imperative to extract the required traffic information from the CCTV footage. It can

beusedtoisolatetherequiredinformationfromrestoftheimage.Thereareseveraledgedetectiontechniquesavailable .Theyhavedistinctcharacteristicsintermsofnoisereduction,detectionsensitivity,accuracyetc.Amongthem,Prewi tt[7], canny [8],Sobel [9], Roberts and LOG are most accredited operators. It has been observed that the Canny edgedetector depicts higher accuracy in detection of object with higher entropy, PSNR(Peak Signal to Noise Ratio),MSE(Mean Square Error) and execution time compared with Sobel, Roberts, Prewitt, Zero crossing and LOG [10-12].

In this paper, a system in which density of traffic is measured by comparing captured image with real timetraffic information against the image of the empty road as reference image is proposed. Here, in figure 1, the blockdiagramfor proposedtraffic controltechnique isillustrated

Implementation Tensor flow Tensor Flow, an open-source, free framework, is utilized for dataflow and distinguishable programming across a range of tasks. It is a symbolic math framework that is also used by machine learning programmers that use neural networks. It is utilized by Google for purposes of research and manufacturing. To work in machine learning, it is a requirement in the industry to have TensorFlow experience. The Google Brain team created TensorFlow for usage within Google. On November 9, 2015, it was made available under the Apache 2.0 open-source licence.

TensorFlow may operate on an assortment of CPUs and GPUs thanks to available CUDA and SYCL enhancements enabling general-purpose computation on graphics processors. TensorFlow is supported by Linux 64-bit, macOS, Windows, as well as mobile operating systems including Android and iOS. Computing might be easily distributed across a variety of platforms (CPUs, GPUs, and TPUs) including PCs, server clusters, mobile devices, and edge devices thanks to its modular design. TensorFlow calculations are represented by autonomous dataflow graphs.

Pandas

Pandas serve as an open-source Python toolkit that provides outstanding performance data analysis and manipulation tools utilizing its powerful data structures. Python was primarily employed for data munging and preprocessing. On analysis of data, it had little of an effect. Pandas discovered the answer. No matter where the data came from, we may use Pandas to carry out the five typical steps of data processing and analysis: prepare, modify, model, and evaluate. Many academic and professional fields, including finance, economics, statistics, analytics, etc., use Python with Pandas.

Numpy

NumPy is a general-purpose library for managing arrays. It provides an extremely quick multidimensional array object and also the ability to interact with such arrays. This Python package is fundamental to scientific computing.

Matplotlib

Publication-quality graphics are produced in a variety of tangible formats and cross-platform interactive environments using the Python 2D plotting package Matplotlib. Matplotlib can be used with several graphical programming toolkits, the Python and IPython shells, the Jupyter notebook, web application servers, and Python scripts. Matplotlib tries to render simple things straightforward while making challenging things doable. You can make graphs, histograms, power spectra, bar charts, error charts, scatter plots, and many more with merely a few lines of code. For instances, view the sample plots and thumbnail galleries. The pyplot package provides a MATLAB-like interface for simple plotting, especially when utilized in the context of IPython. Power users are given total control over line styles, font settings, axis characteristics, etc. through an object-oriented approach or other technique.

MODULES

Toimplementthisprojectwehavedesignedfollowingmodules

- 1) GenerateWSNNetwork:usingthismodulewewillgeneratesomerandomWSNnodesaswe don'thaverealsensors sowe aregeneratingvirtualnodes
- 2) Find Optimal Cluster Size: using this module we will calculate X and Y location of each node and then using formula given in paper we will calculate Optimal number of cluster.
- 3) Run Modified FCM: using this module we will cluster all nodes using FCM and ifcluster size < cluster threshold then we will call Modified FCM. (all this technique weareshowinginabovecodescreens)
- $\label{eq:constraint} 4) \quad Rotation Cluster Head Selection: using this module we will select cluster head for each cluster of the select cluster of the$
- 5) Route Packets to Base Station: using this module we will select Source IOT and thenfinditsclusterheadandthenclusterheadwillfindnearest neighbourtoroutepackettobase station
- 6) Energy Consumption Graph: using this module we will plot energy consumption forproposeandexistingpathselectionbasedondistance

Results and Analysis

Torunprojectdoubleclickon'run.bat'filetogetbelowscreen insamecluster.Intext

areawecanseewhichnodeisinwhichcluster.Nowclickon'RotationClusterHeadSelection'buttonto selectcluster headforallclustersand getbelowoutput.





In aboves creen from drop down box I am selection node 11 and then click on `Route Packetto Base Station' button toget below output.



In above screen black line indicate data sending from source to base station where MN 11 is the source node and CH2 is the cluster and MN6 is the nearest neighbour to base station. Same path details we can see int ext area also and similarly you can select any source node and route packets to destination. Now click on 'Energy Consumption Graph' but tont oget below graph

TESTING AND VALIDATION

S. No.	Test Case	Excepted Results	Results
1	No. of nodes	Enter required no. of nodes	Pass
2	Node id	Enter no. of id's	Pass
3	Generate WSN	It forms the network	Pass
	Network		
4	Existing AODV	IT generates the existing path	Pass
5	Route packet to BS	It generates the optimal path	Pass
6	Energy	Shows efficient between	Pass
	consumption graph	existing and proposed	

Table.1. Test Data

If we give node id more than given number of nodes then it will not generate any path between nodes.



CONCLUSION

In this significant work, we propose an improved energy-efficient clustering protocol (IEECP) to prolong the lifetime of WSN-based IoT network through overcoming the problems of the clustering structure that adversely affect the protocol performance. Evidently, the proposed protocol reduces and balances the energy consumption of nodes by improving the clustering structure. Hence, the IEECP is deemed suitable for networks that require a longer lifetime. In general, the results yield that the IEECP performs better than the existing protocols. Our proposed protocol will be a beneficial contribution to the field that will enhance the dailyoperationsinmanyareasoflife, which utilize WSN in the IoT world. The energy consumption of the network is analyzed to compute the optimal number of clusters based on the distance to the CH in the case of the overlapping clusters. Then. the modified FCM algorithm (M-FCM) is proposed by combining it with a centralized mechanism to form static and balanced clusters. Finally, a new CH sele ction-rotationalgorithm(CHSRA)ispresentedbyintegratingtheback-off timer mechanism for the CH selection with the rotation mechanism for CH rotation. The CHSRA has relied on a new objective function for selecting CHs in optimal locations tobalance the energy consumption among CHs for the clusters. Furthermore, it has relied on anew dynamic threshold for CH rotation within members of clusters to balance the energy consumption for the successive CHs in the cluster. In future work, we aim to enhance the protocol by improving the FCM algorithm concerning the random initial selection. Moreover, we believe that improving the objective function of CH selection through the reliance onweighted energy-based distance for adjacent CH sisal socrucially significant.

FUTURE SCOPE

The future scope of an improved energy-efficient clustering protocol for WSN-based IoTsystems is promising and encompasses several areas of development. Here are some potentialavenuesforfuture researchandadvancements:

Advanced Machine Learning Techniques: Integration of machine learning algorithms, such asreinforcement learning or deep learning, can further optimize the clustering process. Thesetechniques can learn from network data and make intelligent decisions regarding cluster headselection, energymanagement, and routing, leading to even more energy-efficient protocols.

IntegrationofRenewableEnergySources:Futureclusteringprotocolscanexploretheintegrationofrenewableenergyso urces, suchassolarorwind, topowerthesensornodes. This would reduce dependence on battery power and enhance the energy sustainability of IoTdeployments, extending the network lifetime.

DynamicAdaptationtoHeterogeneousEnvironments:IoTdeploymentsoftenencounterdiverseenvironmentalconditi ons,suchasvaryingnodedensities,mobilitypatterns,orinterference levels. Future protocols can focus on dynamically adapting clustering strategiesbasedonthesechangingenvironmentstooptimizeenergyefficiency.

IntegrationwithEdgeandFogComputing:Incorporatingedgeandfogcomputingcapabilitiesintoclusteringprotocolsca nenablelocaldataprocessingandreducecommunicationoverhead. This can further conserve energy and extend the network lifetime by minimizing unnecessarydatatransmissions to the central server.

Security and PrivacyConsiderations:AsIoTsystemsbecome increasingly interconnected and handle sensitive data, security and privacy concerns become paramount. Future clustering protocols should address these challenges by incorporating robust encryption, authentication mechanisms, and privacy-preserving techniques to ensure the integrity and confidentiality of data.

REFERENCES

- J. Shen, A. Wang, C. Wang, P. C. K. Hung, and C.-F. Lai, "An efficient centroid-basedrouting protocol for energy management in WSN-assisted IoT," IEEE Access, vol. 5, pp.18469–18479,2017.
- [2] V.Reddy and P.Gayathri, "Integration of Internet of Thingswith wireless sensornetwork," Int.J. Electr.Comput.Eng., vol.9, no.1, pp.439–444, 2019.
- [3] H. P. Gupta, S. V. Rao, A. K. Yadav, and T. Dutta, "Geographic routing in clusteredwireless sensor networks among obstacles," IEEE Sensors J., vol. 15, no. 5, pp. 2984–2992, May2015.
- [4] Q. Wang, S. Guo, J. Hu, and Y. Yang, "Spectral partitioning and fuzzy C-means basedclusteringalgorithmforbigdatawirelesssensornetworks," EURASIPJ.WirelessCommun.Netw.,vol.2018,no.1,pp.1–11,Dec.2018.
- [5] S. Dehghani, B. Barekatain, and M. Pourzaferani, "An enhanced energy- aware cluster-based routing algorithm in wireless sensor networks," Wire- less Pers. Commun., vol. 98, no.1,pp.1605–1635,Jan.2018.
- [6] A.ShetaandB.Solaiman, "EvolvingahybridK-meansclusteringalgo-rithmforwirelesssensor network using PSO and GAs," Int. J. Comput. Sci. Issues, vol. 12, no. 1, pp. 23–32,2015.
- [7] L.Kong,Q.Xiang,X.Liu,X.-Y.Liu,X.Gao,G.Chen,andM. Y.Wu, 'ICP:Instantaneousclusteringprotocolforwirelesssensornetworks,''Comput.Netw.,vol.101,pp.144– 157,Jun.2016.
- [8] M. S. Tinker and S. Chinara, "Energy conservation clustering in wireless sensor networksfor increased life time," in Proc. 2nd Int. Conf. Adv. Comput. Commun. Eng., May 2015, pp.7–10.
- [9] A. Bouyer, A. Hatamlou, and M. Masdari, "A new approach for decreasing energy inwireless sensor networks with hybrid LEACH protocol and fuzzy C-means algorithm," Int. J.Commun.Netw.Distrib.Syst.,vol.14,no.4,pp.400–412,2015.
- [10] S. Su and S. Zhao, "An optimal clustering mechanism based on fuzzy-C means

forwirelesssensornetworks,"Sustain.Comput.,Inf.Syst.,vol.18,pp.127–134,Jun. 2018.

- [11] S.B.Shah,Z.Chen,F.Yin,I.U.Khan,andN.Ahmad, "Energyandinteroperableawareroutingforthroughputoptimi zationinclusteredIoT-wirelesssensornetworks," FutureGener.Comput.Syst.,vol.81,pp.372–381,Apr.2018.
- [12] Q. Ni, Q. Pan, H. Du, C. Cao, and Y. Zhai, "A novel cluster head selec- tion algorithmbased on fuzzy clustering and particle swarm optimiza- tion," IEEE/ACM Trans. Comput.Biol.Bioinf.,vol.14,no.1,pp.76– 84,Jan.2017.
- [13] H.ElAlamiandA.Najid, "CFFL: Clusterformationusing fuzzylogic forwirelesssensornetworks," in Proc. IEEE/ACS 12th Int. Conf. Comput. Syst. Appl. (AICCSA), Nov. 2015, pp.1–6.
- [14] A. Jain, "Traffic aware channel access algorithm for cluster based wireless sensornetworks," Wireless Pers. Commun., vol.96, no.1, pp.1595–1612, Sep.2017.
- [15] C. Gherbi, Z. Aliouat, and M. Benmohammed, "A novel load balancing schedulingalgorithmforwirelesssensornetworks,"J.Netw.Syst.Man-age.,vol.27,no.2,pp.430–462,Apr.2019.
- [16] Z. Xu, L. Chen, C. Chen, and X. Guan, "Joint clustering and routing design for reliableandefficientdatacollectioninlargescalewirelesssensornetworks," IEEEInternetThingsJ., vol.3, no.4, pp.520–532, Aug. 2016.
- [17] W.R.Heinzelman, A.Chandrakasan, and H.Balakrishnan, "Energy-efficient communication protocol for wireless microsensor networks," in Proc. 33rd Annu. Hawaii Int.Conf.Syst.Sci., Jan.2000, p.10.
- [18] S.A.Sert,A.Alchihabi,andA.Yazici, "Atwotierdistributedfuzzylogicbasedprotocolforefficientdataaggregationinmultihopwirelesssensornetworks," IEE ETrans.FuzzySyst.,vol.26,no.6,pp.3615–3629,Dec.2018.
- [19] Z. M. Zahedi, R. Akbari, M. Shokouhifar, F. Safaei, and A. Jalali, "Swarm intelligencebased fuzzy routing protocol for clustered wireless sensor networks," Expert Syst. Appl., vol.55,pp.313–328,Aug.2016.
- [20] M. Shokouhifar and A. Jalali, "Optimized Sugeno fuzzy clustering algo- rithm forwirelesssensornetworks," Eng. Appl. Artif. Intell., vol. 60, pp. 16–25, Apr. 2017.
- [21] W. B. Heinzelman, A. P. Chandrakasan, and H. Balakrishnan, "An application-specificprotocol architecture for wireless microsensor networks," IEEE Trans. Wireless Commun.,vol.1,no.4,pp.660– 670,Oct.2002.
- [22] M.T.Rahama, M.Hossen, and M.M.Rahman, "Arouting protocol for improving energy efficiency in wireless sensor networks," in Proc. 3rd Int. Conf. Electr. Eng. Inf. Commun. Technol. (ICEEICT), Sep. 2016, pp. 1–6.
- [23] A. Thakkar and K. Kotecha, "Cluster head election for energy and delay constraintapplicationsofwirelesssensornetwork," IEEES ensors J., vol. 14, no. 8, pp. 2658–2664, Aug. 02014.